



## OSB (QUALITY LEVEL 3)

Panel comprised of damp-proof particleboard measuring 16 mm on the outer face, an insulating core of extruded polystyrene (XPS) and an inner face of OSB (oriented strand board) of quality level 3, measuring 10 mm. This panel performs particularly well under damp conditions.

### DIMENSIONS (mm)

LENGTH	WIDTH	THICKNESS
2440	600	66 / 76 / 86 / 106 / 126

*Check availability for other sizes and thicknesses.*

### COMPOSITION

LAYER	COMPOSITION	THICKNESS
INTERIOR	OSB panel	10 mm
CORE	Extruded polystyrene (XPS)	40 / 50 / 60 / 80 / 100 mm
EXTERIOR	Damp-proof particleboard	16 mm

### TECHNICAL INFORMATION

REFERENCE	THERMAL PROPERTIES	LOADS FOR L/250 / kg/m <sup>2</sup>			
		W/m <sup>2</sup> °K	Weight Kgr/m <sup>2</sup>	1220 mm	810 mm
COXH/10-40-16	0.52	18.10	530	1170	1365
COXH/10-50-16	0.44	18.40	681	1360	1516
COXH/10-60-16	0.38	18.80	815	1597	1802
COXH/10-80-16	0.29	19.50	1045	1924	2125
COXH/10-100-16	0.22	20.10	1286	2132	2365

*Highly resistant to damp.*

MOISTURE-RESISTANT

